

# SAFETY DATA SHEET

Revision Date: 11/21/2018 SDS

Section 1 – Identificat	ion	
Product Name:	Sealing Compound Slugs, Part Number SCS-1	
Recommended Use:	For use as a seal against water, dust and air. It noise and sound deadener.	can also be used as a
Manufacturer:	Vapco Products 401 Marshal Road, Valley Park, Mo 63088	
Phone:	844-229-9906 info@VapcoProducts.com www.VapcoProducts.com	
24-hour Emergency	ChemTel USA: 800-255-3924 International: +01 813-248-0585	
Section 2 – Hazard Ide	entification	
GHS Classification:	Acute toxicity – dermal Eye irritation: Carcinogenicity: Specific target organ toxicity – single exposure (lung/respiratory system): Specific target organ toxicity – repeated exposure (lungs):	Category 5 Category 2B Category 1A Category 1 Category 2
GHS Label Element:	<b>^</b>	



Signal Word:

Danger

Hazard Statements:	<ul> <li>H313 May be harmful in contact with skin.</li> <li>H320 Causes eye irritation.</li> <li>H350 May cause cancer via inhalation of dust.</li> <li>H370 Causes damage to organs (lungs/respiratory system) through inhalation.</li> <li>H373 May cause damage to organs (lungs) through prolonged or repeated exposure.</li> </ul>
Precautionary Statements:	<ul> <li>Prevention:</li> <li>P201 Obtain special instructions before use.</li> <li>P202 Do not handle until all safety precautions have been read and understood.</li> <li>P260 Do not breathe dust.</li> <li>P264 Wash hands and skin contact areas thoroughly after handling.</li> <li>P270 Do not eat, drink or smoke when using this product.</li> <li>P280 Wear protective gloves and eye protection.</li> </ul>
	<ul> <li>Response:</li> <li>P301 + P312 + P330 + P331 IF SWALLOWED: Call a doctor if you feel unwell. Rinse mouth. Do not induce vomiting.</li> <li>P302 + P313 + P332 + P352 + P362 + P364 IF ON SKIN: Get medical advice. If skin irritation occurs: Get medical attention. Wash with plenty of soap and water. Difficult to remove material may require the use of mineral spirits to remove residue. Take off contaminated clothing and wash it before reuse.</li> <li>P305 + P337 + P338 + P351 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.</li> <li>P314 Get medical attention if you feel unwell.</li> </ul>
	Storage: P405 store locked up.
	Disposal P501 Dispose of contents in accordance with local/regional/national regulations (see Section 13 for specifics).
Other Hazards:	None known.

## Section 3 – Composition / Information on Ingredients

Chemical Name	CAS Number	Weight %
Limestone	1317-65-3	70-80%
Butene, homopolymer	9003-27-4	10-20%
Hydrous magnesium silicate	14807-96-6	1-10%
Chlorite-group minerals	1318-59-8	1-5%
Crystalline silica (impurity)	14808-60-7	<1%

#### Section 4 – First Aid Measures

Eye:	Flush with water for 15-minutes. Seek medical attention if mechanical irritation occurs.	
Skin:	Remove from skin and wash with soap and water. Difficult to remove material may require the use of mineral spirits to remove residue. Get medical attention if irritation develops.	
Inhalation:	Not applicable.	
Ingestion:	Do not induce vomiting. Get medical attention immediately.	
Most important symptoms and effects, acute and delayed:	May cause eye and skin irritation. May cause damage to skin through prolonged or repeated exposure.	
Physicians:	Treat according to the patient's condition and specifics of exposure.	
Section 5 – Fire Fighting Measures		
Suitable Extinguishing Media:	For small fires use carbon dioxide (CO <sub>2</sub> ), dry chemical or water spray. For large scale fires, use dry chemical, foam or water spray.	

Hazardous combustion products:	Carbon monoxide, carbon dioxide, isobutene and other combustion products are possible.
Protective equipment and precautions:	Self-contained breathing apparatus and protective clothing should be worn in fighting large fires. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep exposed containers cool.

#### Section 6 – Accidental Release Measures

Personal precautions, protective equipment and emergency procedures:	Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.
Environmental precautions:	Prevent further spillage if safe to do so. Keep from discharging into the environment.
Containment / Clean-up:	Wipe or scrape up and contain for salvage or disposal. Dispose of according to state and local laws.

### Section 7 – Handling and Storage

Handling:	Wash hands or exposed areas thoroughly after handling and prior to eating, drinking or smoking. Use personal protective equipment
Storage:	Normal warehouse conditions are acceptable. Keep containers dry.
	Page 3 of 9

Sealing Compound Slugs, Part Number SCS-1 - SDS

#### Section 8 – Exposure Controls / Personal Protection

Exposure Guidelines:

Chemical Name	CAS Number	Туре	Value
Limestone	1317-65-3	ACGIH	10 mg/m <sup>3</sup> total dust
			3 mg/m <sup>3</sup> respirable fraction
		OSHA PEL	15 mg/m <sup>3</sup> total dust
			5 mg/m <sup>3</sup> respirable fraction
Butene, homopolymer	9003-27-4	ACGIH	No established limits
		OSHA	No established limits
Hydrous magnesium silicate	14807-96-6	ACGIH TWA	2 mg/m <sup>3</sup> respirable fraction
		OSHA PEL	20 mppcf
Chlorite-group minerals	1318-59-8	ACGIH TWA	No established limits
		OSHA PEL	No established limits
Crystalline silica (impurity)	14808-60-7	ACGIH TWA	0.025 mg/m <sup>3</sup> respirable
			fraction
		OSHA PEL	$0.1 \text{ mg/m}^3$

Engineering Controls:

Local and general ventilation are recommended.

Personal Protective Equipment:

|--|--|

Eye protection:	Safety glasses recommended.
Skin and body protection:	Gloves recommended to reduce exposure. Suitable gloves include cotton, leather, nitrile rubber, natural rubber or neoprene rubber. Wear appropriate clothing such as long sleeves and pants to reduce exposure
Respiratory protection:	None required if local ventilation is adequate. Where concentrations are above recommended limits as determined by air sampling or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators.

#### Section 9 – Physical and Chemical Properties

Appearance:	Off-white, putty-like solid
-------------	-----------------------------

- Odor: Faint, mild odor
- Odor threshold: Not determined
- pH: Not determined

Freezing/melting point:	Not determined	
Boiling point and range:	Not determined	
Flash point:	Not determined	
Evaporation rate:	Not determined	
Flammability:	Not classified as a flammable hazard	
Lower / Upper flammability:	Not determined	
Vapor pressure @ 25°C:	Not determined	
Vapor density:	Not determined	
Specific gravity:	1.81 g/cm <sup>3</sup>	
Solubility:	Not determined	
Partition coefficient (n-octanol/water):	Not determined	
Autoignition temperature:	Not determined	
Decomposition temperature:	>200°C (392°F)	
Viscosity:	Not determined	
Section 10 – Stability and Reactivity		
Reactivity:	Not reactive.	
Chemical stability:	Stable	
Hazardous reaction possibility:	Hazardous reactions or polymerization will not occur.	
Conditions to Avoid:	None.	
Incompatible materials: Hazardous decomposition products:	Avoid contact with strong oxidizers. Carbon monoxide, carbon dioxide, isobutene and other combustion products are possible.	
Section 11 – Toxicological Information		

Likely routes of exposure: Skin contact Eye contact Inhalation

Acute toxicity:	Product (mixture calculation method)		
5	Oral:	LD <sub>50</sub> >6000 mg/kg	
	Dermal:	LD <sub>50</sub> >2800 mg/kg	
	Inhalation:	LC <sub>50</sub> >12 mg/L	
	Ingredients		
	Limestone		
	Oral:	LD <sub>50</sub> 6450 mg/kg	
	Dermal:	$LD_{50}$ No data	
	Inhalation:	$LC_{50}$ No data	
	Butene, homopolymer		
	Oral:	LD <sub>50</sub> >5000 mg/kg	
	Dermal:	LD <sub>50</sub> >3000 mg/kg (rabbit)	
	Inhalation:	$LC_{50} > 17.3 \text{ mg/L (mist)}$	
	Hydrous magnesium silicate		
	Oral:	LD <sub>50</sub> No data	
	Dermal:	$LD_{50}$ No data	
	Inhalation:	$LC_{50}$ No data	
	Chlorita group minanala		
	Chlorite-group minerals		
	Oral:	LD <sub>50</sub> No data	
	Dermal:	LD <sub>50</sub> No data	
	Inhalation:	$LC_{50}$ No data	
	Crystalline silica		
	Oral:	LD <sub>50</sub> 500 mg/kg	
	Dermal:	LD <sub>50</sub> No data	
	Inhalation:	LC <sub>50</sub> No data	
Skin corrosion / irritation:	Not classified based on available information.		
Eye damage / irritation:	Product		
	No data available.		
	Ingredients		
	Butene, homopolymer		
	Causes eye irritation.		
Respiratory / skin sensitization:	Not classified based on available information.		
Mutagenicity:	Not classified based on	available information.	
Carcinogenicity:	<u>Product</u> No data available		
	ino data avallable		

	Ingredients Crystalline silica (impurity) This product contains >0.1% crystalline silica which is listed as a Group 1 carcinogen by IARC, a known carcinogen by NTP and OSHA and as A2 suspected human carcinogen by ACGIH.	
Reproductive toxicity:	Not classified based on available information.	
STOT – single exposure:	Product No data available.	
	<u>Ingredients</u> Hydrous magnesium silicate May cause damage to organs (lungs/respiratory system) via inhalation.	
STOT – repeated exposure:	<u>Product</u> No data available.	
	<u>Ingredients</u> Crystalline silica May cause damage to organs (lungs) through prolonged or repeated exposure.	
Aspiration hazard:	Not classified based on available information.	
Section 12 – Ecological Information		

Ecotoxicity:	No data available.
Persistence and degradability:	No data available.
Bioaccumulative potential:	No data available.
Mobility in soil:	No data available.
Other adverse effects:	This product does not contain any of the controlled substances listed in the Annexes to the Montreal Protocol at concentrations of $\geq 0.1\%$ .

## Section 13 – Disposal Considerations

Disposal methods:	This product has been evaluated for RCRA hazard class (40 CFR 261) characteristics and does not meet the criteria of hazardous waste if discarded in its purchased form. Do not dispose material into any storm water or sewage system. State or local laws may impose additional regulatory requirements regarding disposal.
Packaging disposal:	Packaging contaminated with butyl sealant should be disposed of in accordance with local regulations. Clean, empty packaging should be taken to an approved waste handling site for recycling or disposal.

Page 7 of 9 Sealing Compound Slugs, Part Number SCS-1 - SDS

### Section 14 – Transport Information

DOT (49 CFR 172.101):	Not subject to DOT regulations.
UN number:	Not regulated as a dangerous good.
UN proper shipping name:	Not regulated as a dangerous good.
Hazard class:	Not applicable.
Packing group:	Not applicable.
Marine pollutant:	No.
Transport in bulk:	Not applicable for product as supplied, according to Annex II of MARPOL 73/78 and the IBC Code.
Ocean Shipment (IMDG):	Not subject to IMDG code.
Air shipment (IATA):	Not subject to IATA regulations.
Special precautions:	Not applicable.

#### Section 15 – Regulatory Information

Contents of this MSDS comply with OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Status:	All chemical substances in this product are either listed or exempt from listing on the TSCA Inventory.
SARA 302:	No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.
SARA 304:	This material does not contain any extremely hazardous substances with SARA Title III, Section 304 reportable quantities.
SARA 311/312 hazards:	Chronic health hazard
SARA 313:	This material does not contain any chemical components with known CAS numbers that exceed the threshold (de minimis) reporting levels established by SARA, Title III, Section 313.
California Proposition 65:	<b>WARNING</b> : This product can expose you to crystalline silica, which is known to the State of California to cause cancer. For more information go to <u>www.P65Warnings.ca.gov</u> .

#### Section 16 – Other Information

#### NFPA:

Date:



Abbreviations and acronyms:

HMIS:



ACGIH - American Conference of Governmental Industrial Hygienists CAS – Chemical Abstracts Service CFR – Code of Federal Regulations DOT – Department of Transportation GHS - Globally Harmonized System HMIS – Hazardous Materials Identification System IATA -- International Air Transport Association IARC - International Agency for Research on Cancer IBC – Intermediate Bulk Container IMDG - International Maritime Dangerous Goods  $LD_{50}$  – Lethal Dose for 50 percent of exposed individuals LC<sub>50</sub> – Lethal Concentration for 50 percent of exposed individuals MARPOL - International Convention for the Prevention of Pollution from Ships (Maritime Pollution) mppcf – million parts per cubic foot MSDS - Material Safety Data Sheet MSHA - Mine Safety and Health Administration NFPA - National Fire Protection Association NIOSH - National Institute for Occupational Safety and Health NTP - National Toxicology Program OSHA - Occupational Safety and Health Administration PEL – Permissible Exposure Level RCRA - Resource Conservation and Recovery Act of 1976 SARA - Superfund Amendments and Reauthorization Act SDS – Safety Data Sheet STOT - Specific Target Organ Toxicity TSCA - Toxic Substance Control Act of 1976 UN – United Nations Sections 2, 3, 8, 11, 15 and 16 were updated from the SDS dated 6-22-**Revision information:** 2015 to reflect updated information from chemical ingredient suppliers. Prepared by: Vapco Products Nov. 21 2018

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate. It is the responsibility of the user to comply with all federal, state and local laws and regulations.

> Page 9 of 9 Sealing Compound Slugs, Part Number SCS-1 - SDS