



May 30, 2019 TECHNICAL DATA REPORT

See SDS for complete safety/technical data

VAPCO PART NO.

Part Number

Size

SCC-1

3/8" X 25' 12/cs

SEALING COMPOUND CORDS

INSULATION/ SEALING

DESCRIPTION

SEALING COMPOUND CORDS are 3/8", water resistant and dust resistant compound cords used for sealing long gaps. Each of the five cords peel easily from the 25' roll. Remains flexible at -30°F and will not flow below 350°F. May be painted.

FEATURES AND BENEFITS

 Seals Against Air, Dust and Moisture

· Seals Windows, Air Ducts, Adaptors and Extensions

SPECIFICATIONS

Appearance: Off-white, putty-like solid | **Odor:** Faint, mild odor | Flammability: Not classified as a flammable hazard | Specific

Gravity: 1.78 g/cm3 | Decomposition Temperature: >200°C (392°F)

LABEL INFORMATION

SEALING COMPOUND CORDS are a non-hardening sealer used to seal against water, dust and air intrusion. Also used for sound deadening applications.

DIRECTIONS: Simply peel and press into place. Adheres to clean surface.

DANGERS: Read and understand the product's label and Safety Data Sheet.

May be harmful in contact with skin. Causes eve irritation. May cause cancer via inhalation of dust. May cause damage to organs (lungs) through prolonged or repeated exposure.



Health	1
Flammability	1
Reactivity	Ô
Personal	



First Aid Measures

Inhalation: Not applicable. Skin contact: Remove from skin and wash with soap and water.

Difficult to remove material may require the use of mineral spirits to remove residue. Seek medical attention if irritation persists.

Eye Contact: Flush with water for 15-minutes. Seek medical attention if irritation persists.

Ingestion: Do NOT induce vomiting. Seek immediate medical attention.

Precautions

Keep out of reach of children.

Wash hands or exposed areas thoroughly after handling and prior to eating, drinking or smoking. Use personal protective equipment. Safety glasses and gloves recommended to reduce exposure.

Storage

Keep out of reach of children.

Normal warehouse conditions are acceptable. Keep containers dry.

In Case of Fire

For small fires use carbon dioxide (CO2), dry chemical or water spray. For large scale fires, use dry chemical, foam or water spray.

Disposal

Dispose of in accordance with federal, state, and local regulations. Do not dispose material into any storm water or sewage system.

SEALING COMPOUND CORDS CONTAINS (CAS#): Limestone (1317-65-3), Butene, homopolymer (9003-29-6)