



# PVC SPRAY 'N LOCK

## LOCKS PIPES AND FITTINGS PERMANENTLY

**PRESSURE TESTED TO 215 PSI**

**HEAT TESTED TO 135°F**

**CERTIFIED NOT TO NEGATIVELY  
IMPACT THE POTABILITY OF WATER**



Aim Your iPhone's  
camera at QR Code.

### PROPER APPLICATION

**COMPLETELY SATURATED**



FOR A WATER AND PRESSURE  
TIGHT BOND, **ENSURE THAT  
BOTH PIPE AND JOINT ARE  
SATURATED** WITH PRODUCT  
BEFORE FITTING AND **WAIT 60  
FULL SECONDS BEFORE  
TESTING.**

**NOT A CEMENT OR GLUE**

**NO PRIMER OR DAUBERS REQUIRED**

### PROPER APPLICATION COMPLETELY SATURATED



### INCORRECT APPLICATION

**Gaps** in spray coverage will adversely affect  
the bonding power of the product. Ensure that  
both pipe and fitting are completely saturated  
with product before joining.

AVAILABLE IN BOTH  
INDUSTRY PURPLE AND  
PROFESSIONAL CLEAR



VISIT [WWW.PVCSPRAYNLOCK.COM](http://WWW.PVCSPRAYNLOCK.COM) FOR MORE INFORMATION, VIDEOS AND INSIGHTS.