



VAPCO PART NO.

Part Number **Size**
 LPO-ITA 12oz Aerosol

LOOSEN IT

AEROSOL / PENETRATING LUBRICANT

DESCRIPTION

LOOSEN IT penetrating lubricant is a powerful non-flammable, multiple-action penetrate and protective shield. Can be used on either dry or wet surfaces. To ensure adequate protection, periodic checks should be made to determine the need for reapplication.

FEATURES AND BENEFITS

- Prevents Rust
- Non-Flammable
- Cleans & Lubricates
- Frees Seized Metal Parts

SPECIFICATIONS

Form: Brown to Amber Spray | **Odor:** Petroleum solvent odor | **Initial Boiling Point and Boiling Range:** > 180°F (82°C) | **Flash Point:** > 110°F (43°C) | **Flammability:** Extremely Flammable Aerosol | **Evaporation Rate:** Slow | **Relative Density (H2O=1):** 0.80 - 0.84 @ 77°F (25°C) | **Solubility in Water:** 0% in water

LABEL INFORMATION

LOOSEN IT will loosen threads, tighten fitted parts, sliding and rotating parts, bolts, hinges and pins which have been “frozen” by corrosion. Protects against renewed corrosion. This product forms a powerful, multiple-action protective shield against the harmful effects of moisture and corrosion. It protects electrical gear, metal and other surfaces from deterioration by displacing water and moisture. It seals all surfaces with a complete molecular film. It preserves equipment, thus reducing repair and maintenance costs. Lubricates, loosens dirt, scale and other corrosive elements; never becomes dry, brittle or hard. Protects the properties of insulating substances and does away with wicking. The conductivity of commutators and contacts is protected. Can be used on either dry or wet surfaces. To insure adequate protection, periodic checks should be made to determine the need for reapplication.

DIRECTIONS: Read all warnings and directions before using. Spray liberally directly on areas to be treated. Reapply periodically as required.

DO NOT puncture, incinerate (burn) or store container above 122°F (50°C). High temperatures may cause the container to burst.

WARNING: This product contains Trichloroethylene (79-01-6), which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

Health	1
Flammability	3
Reactivity	0
Personal	A



CONTAINS

LOOSEN IT CONTAINS (CAS#) :Mineral Seal Oil (64741-44-2), Petroleum Distillates, Hydrotreated light (64742-47-8), Propane/n-Butane (68476-86-8) Distillates (Petroleum) solvent dewaxed heavy paraffinic (64742-56-8), Ethyl Acetate (141-78-6).

First Aid Measures

Inhalation: Move to fresh air. If breathing is difficult, administer oxygen. If not breathing administer artificial respiration. **Seek immediate medical attention.**

Skin Contact: Immediately wash with soap and water for 15 minutes. Remove contaminated clothing and shoes immediately. **Seek medical attention if irritation persists.**

Eye Contact: Immediately flush with water for 15 - 20 minutes while holding eyelids open. **If eye irritation persists, consult a doctor.**

Ingestion: If swallowed: **Immediately call a poison center or doctor.** Do **NOT** induce vomiting.

Precautions

PRECAUTIONS: Extremely Flammable Aerosol. Contains gas under pressure: May explode if heated. Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash hands thoroughly after handling.

Storage

Keep out of reach of children. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place.

In Case of Fire

Use dry chemical, foam, or Carbon Dioxide (CO2) as extinguishing media. Do not use water spray/stream. Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires.

Disposal

Dispose of in accordance with federal, state, and local regulations. Do not reuse, puncture, or incinerate container. Wrap container and place in trash collection. Product should be fully characterized prior to disposal (40 CFR 261).